

KM-LM65-F400

65" UHD LED Monitor

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



Features:

- 4K Ultra-HD resolution
- Suitable for continuous 24/7 operation
- 8ms response time for no motion blur, judder or ghosting
- 1.07G colors for realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° extra-wide viewing angle for overall viewing performance
- Professional thermal design to extend equipment lifespan



Technical Specification

Display

Screen Size	65"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness	350cd/m ²
Contrast Ratio	1200:1
Display Color	1.07G(8 Bits+FRC)
Viewing Angle	178°(H)/178°(V)
Response Time	8ms
Refresh Rate	60Hz

Signals

Input	HDMI 2.0×1, HDMI1.4×1, USB 2.0×1, VGA×1, Audio in×1, RS232×1
Output	Speaker×2 (7W)

General

Power Supply	AC100-240V, 2.5A, 50/60 Hz
--------------	----------------------------

Consumption (Standard)	190W	
Consumption (Standby)	< 0.5W	
Net Weight	18.6Kg	
Gross Weight	24.4Kg	
Bezel Width	8.24mm (U), 2.9mm (L/R), 22.62mm (B)	
VESA	300×300mm	
Dimension without base (W×H×D)	1446.3×838.4×77.6mm (56.9"×33"×3.1")	
Package(W×H×D)	1600×995×174mm (63"×39.2"×6.9")	
Work Environment	Temperature	0°C~40°C
	Humidity	10%~80%

Accessory

Standard	Power cable, remote control, pedestal
Optional	Hanging bracket

KM-LM65-F400

65" UHD LED Monitor

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.

Dimensions(mm)

